

ProCash 285



Monofunctional cash dispenser for outdoor installations

Simple yet sophisticated

The ProCash 285 is a new weatherized cash dispenser in Wincor Nixdorf's ProCash product family. The elegant machine comes with the familiar capacity and reliability that ProCash systems offer. It combines a small footprint with superior German technology.

Robust and compact design

The rearload system is ideal for use in outdoor environments, where a robust machine type is needed. With a through-the-wall installation, the compact system fits easily into wall openings and is ideal for places where space is a limiting factor. The system's performance and resilience are reliable, proven to reduce queues and speed up transaction throughput, and as a result ensure easy maintenance and satisfied customers.

Reliable and versatile technology

The system also comes with flexible hardware and software configurations that can be customized to your needs and are open for upgrades and module modifications in the future. In addition, German engineering guarantees maximum availability as well as efficient transactions for customers.

Intuitive usability

Redefine the consumer experience with the ProCash 285. The system features a highly user-friendly display interface with illuminated customer guidance for a hassle-free consumer experience and operational efficiency.

A comprehensive security suite

An anti-manipulation card slot, anti-skimming module, biometric solutions as well as portrait and cash slot cameras - these features address security concerns, enhance consumer confidence and maintain the integrity of your system.

WINCOR
NIXDORF



Services

Wincor Nixdorf's fast, professional manufacturer service is available as an option for the ProCash 285 as part of the complete solution offer. Tailored services enable the highest possible system availability and security worldwide due to standardized service processes and efficient remote management based on the Wincor Nixdorf eServices Platform®. By request retailers can hand over their complete IT operations and the control of their cash processes to Wincor Nixdorf's service organization.

Consulting and integration

Wincor Nixdorf offers a fast and optimal business implementation – from analysis and concept design through to optimal deployment and integration in individual customer scenarios. In Professional Services from Wincor Nixdorf you find an ideal partner for implementing your retail banking process and IT strategy.

Published by
Wincor Nixdorf International GmbH
 Heinz-Nixdorf-Ring 1
 33106 Paderborn
 Germany
 Phone: +49 (0) 52 51 / 6 93-30
 Fax: +49 (0) 52 51 / 6 93-77 30
 info.banking@wincor-nixdorf.com
 www.wincor-nixdorf.com

© Wincor Nixdorf International GmbH

Order No. R10150-J-2744-1-7600
 Printed in Germany, April 2013

TECHNICAL DATA

General

Installation types

- Outdoor/Indoor as rearload
- TTW

Chassis

- Illuminated logo panel (optional)
- Customers guided by optical indicators at all input and output modules

Banknote processing

Cash out module

- Withdrawals of up to 60 notes in a bundle
- Banknote reject/bundle retract

Banknote storage

- 2 / 4 cassettes
- Fill level indicator
- Scalable cassette concept: Lock, lead seal, tamper indicator
- Retract/reject cassette with 2 compartments

Customer interaction

Display

- 15" TFT LCD Display
- Full-colour screen
- Semi high brightness display
- 8 soft keys and/or touch display

Keyboard

- EPP, PCI certified
- supports Remote Key Loading

Card processing

- Motorized hybrid card reader: LoCo/HiCo, magnetic read/write, read/write Smart/IC card, track down
- DIP card reader
- EMV certified

Printers

- Receipt printer (Thermal)
- Journal printer (Thermal or Impact)

Audio

- Loudspeakers, headset jack with adjustable volume

Security

Cash security

- Safes: UL 291 Level 1, CEN L

Data and software security

- Anti-Manipulation Card Slot
- Anti-Skimming II Module
- Privacy display filter for the monitor

Identity and access control

- Mechanical and electronic locks
- Biometric options: Fingerprint (optional)
- PIN shield (optional)
- Intelligent operator authentication

Security monitoring

- Cash slot and portrait camera

Multifunctionality

Barcode reader

- 1D or 2D Barcode

Service

Service Screen

- 8.4" LCD Touch

Operation

Environmental conditions

- Temperature range
 - Inside: 5 °C to 40 °C
 - Outside: -40 °C to 50 °C
- Relative Humidity: 5 % to 85 %

Technical details

- Supply voltage range: 110 – 120V; 220 – 240V
- Mains frequency 50/60 Hz
- Uninterruptable Power Supply (optional)

Software

Operating System

- Windows XP Professional SP3
- Windows 7

Weight

- 427 kg (with UL safe)
- 505 kg (with CEN L safe)